





<https://www.wago.com/887-957>



Item includes

 <p>Item no.: 221-412 75</p> <p>COMPACT Splicing Connector; for all conductor types; max. 4 mm²; 2-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent</p>	 <p>Item no.: 221-413 50</p> <p>COMPACT Splicing Connector; for all conductor types; max. 4 mm²; 3-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent</p>	 <p>Item no.: 221-415 25</p> <p>COMPACT Splicing Connector; for all conductor types; max. 4 mm²; 5-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent</p>	 <p>Item no.: 221-500 1</p> <p>Mounting carrier; 221 Series - 4 mm²; for DIN-35 rail mounting/screw mounting; orange</p>
<p>Item no.: 221-612 40</p> <p>COMPACT Splicing Connector; for all conductor types; max. 6 mm²; 2-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 6,00 mm²; transparent</p>	<p>Item no.: 221-613 30</p> <p>COMPACT Splicing Connector; for all conductor types; max. 6 mm²; 3-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 6,00 mm²; transparent</p>	<p>Item no.: 221-615 15</p> <p>COMPACT Splicing Connector; for all conductor types; max. 6 mm²; 5-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 6,00 mm²; transparent</p>	

Physical data

Width	260 mm / 10.236 inches
Height	63 mm / 2.48 inches
Depth	155 mm / 6.102 inches